



FOR AES PROFESSIONAL AND AES LiFePO₄ MOBILE & INDUSTRIAL BATTERIES

LYNK LITE Communication Gateway aggregates and displays in real-time the State of Charge for AES PROFESSIONAL and AES LiFePO₄ batteries. Unlock the full potential of these lithium batteries by integrating them with inverter-chargers, on and off-board chargers, displays, load centers, motor controls, PLCs, and telematics to optimize system performance.

Improve system integration using multiple communication interfaces and CAN-based protocols. LYNK ACCESS Software for LYNK LITE includes device programming, firmware uploads, battery digital signal simulation, and data analysis to reduce development time and effort.

REAL-TIME DATA	State of Charge (SoC), voltage, temperature and battery status is communicated in real time to on-board devices.
FASTER CHARGING	Up to 25% faster 0% to 100% SoC charging with dynamic charge management.
COMMUNICATION	Configurable - CANopen, Serial CAN, J1939, RV-C
FULL COMPATIBILITY	Battery related settings are automatically programmed for multiple brands of industrial chargers.
STATUS VIEW	At-a-glance SoC LEDs, communication status LED.
MAXIMIZE THE BATTERY	Internal cell balancing is optimized, enabling the highest usable capacity and true 100% depth of discharge over the entire life of the battery.
SIMPLE SERVICE	Download data logs, upload battery firmware, and more.

UNLOCK THE FULL POTENTIAL OF AES PROFESSIONAL AND AES LiFePO₄ BATTERIES.

SPECIFICATIONS

DEVICE	LYNK II COMMUNICATION GATEWAY
Part Number	950-0040
L x W x H	95 x 56 x 30 mm / 4.7 x 2.2 x 1.2 in
Weight	0.1 kg / 0.2 lb
IP Rating	IP65
Temperature	Operating: -20°C to 50°C (-4°F to 122°F) / Storage: -40°C to 85°C (-40°F to 185°F)
Humidity	Operating: < 95%, Non-condensing / Storage: < 95%
Mounting	Built-in Surface / Flush Mount Bracket
Display LEDs	1 x LYNK Port Connection LED, 1 x CAN Status LED
COMMUNICATION PORTS	
LYNK Ports	IEC (M12 -5 PIN)
Memory	Internal SD Memory Card
CAN Out	IEC (M12 -5 PIN)
DATA INTERFACE	
USB Device	Type-B Mini
POWER INPUT	
LYNK Port	12 V Nominal
USB Device	5 V
STANDARDS	
Marking	CE
COMPATIBLE BATTERIES	
AES LiFePO ₄	130 Ah 48 V (12-48-6650), 57 Ah 48 V (14-48-3000), 76 Ah 36 V (14-36-3000), 175 Ah 24 V (12-36-6700), 110 Ah 24 V (14-24-2800)
AES PROFESSIONAL	30 Ah 48 V (DLP-GC2-48V), 30 Ah 36 V (DLP-GC2-36V), 60 Ah 24 V (DLP-GC2-24V), 120 Ah 12 V (DLP-GC2-12V)



LYNK ACCESS - Windows 64 bit

Download from discoverlithium.com

- Configure LYNK LITE for Devices
- Battery Diagnostics
- Upload Battery Firmware
- Download Battery Data
- Analyze and Visualize Battery Data

ACCESSORIES - LITHIUM PROFESSIONAL

- 950-0035 COMM Cable (0.4 m / 15.75 in)
- 950-0036 COMM Cable (1.8 m / 70.87 in)
- 950-0037 COMM Cable (7.6 m / 299.25 in)
- 950-0038 COMM T Connector with COMM Cable (0.4 m / 15.75 in)
- 950-0041 COMM T Connector

ADVANCED INTEGRATION

Turn a good system into a great one with ultra-fast charging, real-time status, predictive equipment control and diagnostics.

- SoC Display
- Auto Programming of Charge Parameters
- Configurable COMMs
- SD Card Memory
- USB Device
- Download Battery Data
- Upload Battery Firmware

AVAILABLE DEVICE CONFIGURATIONS

Download from discoverlithium.com

- Serial CAN
- CANopen
- RV-C
- Victron Energy - Color Control GX, Venus GX, VE.CAN Devices
- SPE Chargers
- CAN Devices
- Others



#7 -13511 Crestwood Place, Richmond, BC, V6V 2E9, Canada

+ 1.778.776.3288

info@discoverlithium.com

discoverlithium.com